

Inhibited Propylene Glycol Heat Transfer Fluid

Process Applications

- HVAC/R
- Boilers and heat exchangers
- Energy applications
- Geothermal energy
- Cooling towers
- Process cooling & heating
- Line heaters
- Winterization
- Solar Applications
- Ice & snow melting systems
- Plastic extrusion

■ Dynalene EG-V1 Overview

Dynalene EG-V1 is an inhibited ethylene glycol heat transfer fluid which offers users a stable, efficient, and aluminum-safe product for applications where freeze protection is needed. Properly used and maintained, Dynalene EG-V1 offers excellent thermophysical properties all while protecting your system from corrosion and degradation for years.

Dynalene EG-V1's inhibitor package is specifically formulated to protect systems using aluminum materials and alloys even at temperatures > 60°C.

■ Corrosion Protection

Dynalene EG-V1 utilizes a unique corrosion inhibitor package, which is made from non-toxic raw materials. This inhibitor offers superior corrosion protection for most metals including aluminum, carbon steel, brass, copper, stainless steel, and cast iron by creating a corrosion-preventing passive layer on the surface that contacts the Dynalene EG-V1. The inhibitor also stabilizes the pH of the fluid. **To ensure the inhibitor package provides the best corrosion protection, Dynalene sells this product as pre-mixed solutions. Please contact Dynalene if you are interested on-site dilution of Dynalene PG-V1.**

■ Benefits of Choosing Dynalene EG-V1

- Pre-mixed solutions
- Custom blends
- Dyes available: yellow, red, blue, pink and fluorescent green
- Can be re-inhibited
- Proven performance
- Available worldwide
- Cost-effective
- Total fluid care option

■ Dynalene's Fluid Care Program

Coupling our Dynalene fluids with a fluid care program can extend the life of your systems significantly. We offer yearly testing of the heat transfer fluid in your system and can track the changes in the fluid year to year so adjustments can be made to keep your systems working at its best.

Recommended Temperature Range:

-51°C (-60°F) to 90°C (194°F)

Required Concentrations of Dynalene EG-V1 for Burst Protection:

Temperature		Vol% Dynalene EG-V1 For Burst Protection
°C	°F	
-6	25	12
-13.2	8	20
-18	-2	24
-23	-9	28
-26	-14	30
-32	-25	33
< -40	< -40	35

■ Properties of Dynalene EG-V1

A comprehensive list of all thermo-physical properties of Dynalene EG-V1 can be found on pages 2, 3, 4, and 5. For health and safety information or to request a Safety Data Sheet, contact our Dynalene sales representatives.

Composition:	Ethylene glycol, inhibitors
Appearance:	Clear, colorless
Odor:	Little or none

pH:	10.0-11.0
Flash Point:	None for concentrations <85%

■ Quantity & Availability

Dynalene EG-V1 is offered in 1, 2.5, 5, 30, 55, and 265-gallon containers as well as 5,000-gallon tankers. Pricing depends on quantity, and Dynalene, Inc. will work with you to try to fit your budget.

General Properties

Vol. % Dynalene EG-V1	Wt. % Dynalene EG-V1	Freeze Point °F	Freeze Point °C	Boiling Point °F	*Reserve Alkalinity (mL)	Specific Gravity 22°C (72°F)
0	0.0	32	0	212	0	1.000
5	5.2	29	-1.7	212	≥ 0.5	1.005
10	10.5	26	-3.3	212	≥ 1.0	1.010
15	15.6	23	-5	212	≥ 1.5	1.015
20	20.8	19	-7.2	213	≥ 2.0	1.020
21	21.8	17	-8.3	213	≥ 2.1	1.021
22	22.9	17	-8.3	213	≥ 2.2	1.022
23	23.9	16	-8.9	213	≥ 2.3	1.023
24	24.9	15	-9.4	213	≥ 2.4	1.024
25	25.9	14	-10.1	214	≥ 2.5	1.025
26	27.0	13	-10.6	214	≥ 2.6	1.026
27	28.0	12	-11.1	214	≥ 2.7	1.027
28	29.0	10	-12.2	215	≥ 2.8	1.028
29	30.1	9	-12.8	216	≥ 2.9	1.029
30	31.1	8	-13.3	216	≥ 3.0	1.030
31	32.1	7	-13.9	216	≥ 3.1	1.031
32	33.1	5	-15.0	216	≥ 3.2	1.032
33	34.1	4	-15.6	216	≥ 3.3	1.032
34	35.1	2	-16.7	217	≥ 3.4	1.033
35	36.1	1	-17.2	217	≥ 3.5	1.034
36	37.2	-1	-18.3	217	≥ 3.6	1.035
37	38.2	-3	-19.4	218	≥ 3.7	1.036
38	39.2	-4	-20.0	218	≥ 3.8	1.037
39	40.2	-6	-21.1	219	≥ 3.9	1.038
40	41.2	-8	-22.2	219	≥ 4.0	1.039
41	42.2	-10	-23.3	219	≥ 4.1	1.040
42	43.2	-12	-24.4	219	≥ 4.2	1.041
43	44.2	-14	-25.5	219	≥ 4.3	1.042
44	45.2	-16	-26.7	220	≥ 4.4	1.043
45	46.2	-18	-27.8	220	≥ 4.5	1.044
46	47.2	-21	-29.4	220	≥ 4.6	1.045
47	48.2	-23	-30.6	221	≥ 4.7	1.046
48	49.2	-26	-32.2	221	≥ 4.8	1.047
49	50.2	-28	-33.3	222	≥ 4.9	1.048
50	51.2	-31	-35.0	222	≥ 5.0	1.049
51	52.2	-34	-36.7	222	≥ 5.1	1.049
52	53.2	-37	-38.3	223	≥ 5.2	1.050
53	54.2	-40	-40.0	223	≥ 5.3	1.050
54	55.2	-43	-41.7	223	≥ 5.4	1.051
55	56.2	-46	-43.3	223	≥ 5.5	1.052
56	57.2	-49	-45.0	224	≥ 5.6	1.053
57	58.2	-53	-47.2	224	≥ 5.7	1.054
58	59.2	-56	-48.9	224	≥ 5.8	1.054
59	60.2	<-60	-51.1	225	≥ 5.9	1.055
60	61.2	<-60	-51.1	225	≥ 6.0	1.055
65	66.1	<-60	-51.1	227	≥ 6.5	1.057
70	71.0	<-60	-51.1	230	≥ 7.0	1.057
75	75.9	<-60	-51.1	238	≥ 7.5	1.058
80	80.8	<-60	-51.1	246	≥ 8.0	1.059

Viscosity

1 cP= 0.001 Pa·s

Dynalene EG-V1, Viscosity, cP									
Temp, °F	Volume								
	20%	25%	30%	35%	40%	45%	50%	55%	60%
-30									498
-20									299
-10							96.0	140	183
0					40.9	51.1	61.3	88.2	115
10			13.4	20.2	27.0	33.8	40.6	57.4	74.2
20	5.36	7.63	9.89	14.2	18.5	23.2	27.8	38.6	49.3
30	4.23	5.85	7.46	10.3	13.1	16.4	19.7	26.7	33.7
40	3.41	4.58	5.75	7.68	9.60	12.0	14.3	19.0	23.7
50	2.79	3.66	4.52	5.87	7.21	8.96	10.7	13.9	17.1
60	2.32	2.97	3.62	4.59	5.56	6.85	8.13	10.4	12.6
70	1.95	2.45	2.94	3.66	4.38	5.36	6.34	7.93	9.51
80	1.66	2.05	2.43	2.98	3.52	4.28	5.04	6.19	7.34
90	1.43	1.74	2.04	2.46	2.88	3.48	4.08	4.93	5.77
100	1.25	1.49	1.73	2.07	2.4	2.88	3.35	3.99	4.62
120	0.97	1.14	1.30	1.52	1.73	2.05	2.36	2.74	3.11
140	0.78	0.90	1.01	1.16	1.31	1.53	1.75	1.99	2.22
160	0.64	0.73	0.82	0.93	1.04	1.20	1.35	1.51	1.66
180	0.54	0.61	0.68	0.77	0.85	0.97	1.08	1.19	1.29
200	0.46	0.52	0.58	0.65	0.71	0.80	0.88	0.96	1.04
220	0.40	0.45	0.50	0.56	0.61	0.68	0.74	0.80	0.86
240	0.36	0.40	0.44	0.49	0.53	0.59	0.64	0.69	0.73

Thermal Conductivity

1 Btu/hr·ft·°F = 1.73 W/mK

Dynalene EG-V1, Thermal Conductivity, Btu/hr·ft·°F									
Temp, °F	Volume								
	20%	25%	30%	35%	40%	45%	50%	55%	60%
-30									0.171
-20							0.188	0.181	0.174
-10							0.191	0.184	0.176
0					0.211	0.203	0.194	0.186	0.178
10			0.235	0.225	0.215	0.206	0.196	0.188	0.179
20	0.262	0.251	0.239	0.229	0.218	0.209	0.199	0.190	0.181
30	0.267	0.255	0.243	0.233	0.222	0.212	0.201	0.192	0.183
40	0.272	0.260	0.247	0.236	0.225	0.215	0.204	0.194	0.184
50	0.277	0.264	0.251	0.239	0.227	0.217	0.206	0.196	0.186
60	0.281	0.268	0.254	0.242	0.230	0.219	0.208	0.198	0.187
70	0.285	0.272	0.258	0.246	0.233	0.222	0.210	0.199	0.188
80	0.289	0.275	0.261	0.248	0.235	0.223	0.211	0.200	0.189
90	0.292	0.278	0.263	0.250	0.237	0.225	0.213	0.202	0.190
100	0.295	0.281	0.266	0.253	0.239	0.227	0.214	0.203	0.191
120	0.298	0.283	0.268	0.255	0.241	0.228	0.215	0.204	0.192
140	0.306	0.290	0.274	0.260	0.245	0.232	0.218	0.206	0.194
160	0.309	0.293	0.277	0.262	0.247	0.234	0.220	0.207	0.194
180	0.312	0.296	0.279	0.264	0.249	0.235	0.221	0.208	0.195
200	0.314	0.297	0.280	0.265	0.249	0.235	0.221	0.208	0.194
220	0.314	0.297	0.280	0.265	0.249	0.235	0.220	0.207	0.194

1 Btu/lb_m·°F = 4,186 J/kg°C

Specific Heat

Dynalene EG-V1, Specific Heat, Btu/lb·°F									
Temp, °F	Volume								
	20%	25%	30%	35%	40%	45%	50%	55%	60%
-30									
-20									0.799
-10									0.804
0							0.855	0.832	0.809
10					0.898	0.879	0.859	0.837	0.814
20			0.936	0.919	0.902	0.883	0.864	0.842	0.82
30	0.966	0.952	0.938	0.922	0.906	0.887	0.868	0.847	0.825
40	0.968	0.955	0.941	0.925	0.909	0.891	0.872	0.851	0.830
50	0.970	0.957	0.944	0.929	0.913	0.895	0.877	0.856	0.835
60	0.972	0.960	0.947	0.932	0.917	0.899	0.881	0.861	0.840
70	0.974	0.962	0.950	0.935	0.920	0.903	0.886	0.866	0.845
80	0.976	0.965	0.953	0.939	0.924	0.907	0.890	0.870	0.850
90	0.979	0.968	0.956	0.942	0.928	0.911	0.894	0.875	0.855
100	0.981	0.970	0.959	0.945	0.931	0.915	0.899	0.880	0.861
120	0.985	0.975	0.965	0.952	0.939	0.924	0.908	0.890	0.871
140	0.989	0.980	0.970	0.958	0.946	0.931	0.916	0.899	0.881
160	0.993	0.985	0.976	0.965	0.953	0.939	0.925	0.908	0.891
180	0.996	0.989	0.982	0.972	0.961	0.948	0.934	0.918	0.902
200	1.000	0.994	0.988	0.978	0.968	0.956	0.943	0.928	0.912
220	1.003	0.999	0.994	0.985	0.975	0.963	0.951	0.937	0.922
240	1.007	1.003	0.999	0.991	0.982	0.971	0.960	0.946	0.932

1 lb_m/ft³ = 16 kg/m³

Density

Dynalene EG-V1, Density, lb/ft ³									
Temp, °F	Volume								
	20%	25%	30%	35%	40%	45%	50%	55%	60%
-30									67.05
-20							66.46	66.70	66.93
-10							66.35	66.58	66.81
0					65.71	65.97	66.23	66.46	66.68
10			65.00	65.30	65.60	65.86	66.11	66.33	66.54
20	64.23	64.57	64.90	65.19	65.48	65.73	65.97	66.18	66.38
30	64.14	64.47	64.79	65.07	65.35	65.59	65.82	66.02	66.22
40	64.03	64.35	64.67	64.94	65.21	65.44	65.67	65.86	66.05
50	63.92	64.23	64.53	64.80	65.06	65.28	65.50	65.69	65.87
60	63.79	64.09	64.39	64.65	64.90	65.12	65.33	65.51	65.68
70	63.66	63.95	64.24	64.49	64.73	64.94	65.14	65.31	65.47
80	63.52	63.80	64.08	64.32	64.55	64.75	64.95	65.11	65.26
90	63.37	63.64	63.91	64.14	64.36	64.55	64.74	64.89	65.04
100	63.20	63.47	63.73	63.95	64.16	64.35	64.53	64.67	64.81
120	62.85	63.09	63.33	63.54	63.74	63.90	64.06	64.19	64.32
140	62.46	62.68	62.90	63.09	63.27	63.42	63.57	63.68	63.79
160	62.03	62.23	62.43	62.60	62.76	62.90	63.03	63.13	63.22
180	61.56	61.74	61.92	62.07	62.22	62.34	62.45	62.53	62.61
200	61.05	61.21	61.37	61.50	61.63	61.73	61.83	61.90	61.97
220	60.50	60.64	60.78	60.89	61.00	61.09	61.17	61.23	61.28
240	59.91	60.03	60.15	60.25	60.34	60.41	60.47	60.51	60.55

1 psi = 6,895 Pa = 0.069 bar = 0.0681 atm = 51.7 mmHg = 21.7 inH₂O

Vapor Pressure

Dynalene EG-V1, Vapor Pressure, psia									
Temp, °F	Volume								
	20%	25%	30%	35%	40%	45%	50%	55%	60%
100	0.9	0.9	0.9	0.9	0.9				
110	1.9	1.6	1.2	1.2	1.2	1.2	1.1	1.1	1.0
120	1.7	1.7	1.6	1.5	1.5	1.5	1.5	1.5	1.4
130	2.2	2.2	2.1	2.1	2.0	2.0	1.9	1.9	1.8
140	2.8	2.8	2.7	2.7	2.6	2.6	2.5	2.4	2.3
150	3.6	3.6	3.5	3.5	3.4	3.4	3.2	3.0	3.0
160	4.6	4.5	4.4	4.4	4.3	4.2	4.1	4.0	3.8
170	5.8	5.8	5.6	5.4	5.4	5.3	5.2	5.0	4.8
180	7.2	7.1	7.0	6.9	6.7	6.6	6.5	6.2	5.9
190	9.0	8.9	8.7	8.5	8.3	8.2	8.1	7.8	7.4
200	11.0	10.9	10.7	10.5	10.2	10.1	9.9	9.5	9.1
210	13.5	13.5	13.1	12.8	12.5	12.3	12.1	11.6	11.1
220	16.4	16.4	15.9	15.6	15.2	15.0	14.8	14.2	13.6
230	19.8	19.5	19.2	18.8	18.4	17.8	17.8	17.1	16.4
240	23.8	23.4	23.0	22.5	22.0	21.7	21.4	20.6	19.7
250	28.4	27.9	27.4	26.9	26.3	26.0	25.6	24.6	23.5

Product Disclaimer

The information contained in this entire publication is presented in good faith at “no charge” and is believed to be correct as of the date indicated. No representations or warranties are made as to its completeness or accuracy. The information listed is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will the seller be responsible for damages of any nature whatsoever resulting from the use of, or reliance upon, this information or the product to which this information refers. Nothing contained on this page is to be construed as a recommendation to use the product, process, equipment or formulation in conflict with any patent. No representation or warranty, expressed or implied, is made that the use of this product will not infringe any patent.

No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or for any other nature are made with respect to the information, or the product to which the information refers.

Contact Information

Corporate Headquarters

Dynalene, Inc.
 5250 West Coplay Road
 Whitehall, PA 18052
 Phone: 610-262-9686 / 1-877-244-5525
 Fax: 610-262-7437
 Email: info@dynalene.com
 Website: www.dynalene.com

Midwest Location

248 Beinoris Dr
 Wood Dale, IL 60191
 Phone: 1-855-216-7639
 Email: centralsales@dynalene.com

West Location

1701 S 5350 W
 Salt Lake City, UT 84104
 Phone: 1-877-244-5525
 Email: westsales@dynalene.com

Published May 2020